



## Highlights

- True Multi-Touch (Detects up to 32 points simultaneously)
- No Ghost Point
- Low Cost

## PQ Labs Multi-Touch Overlay

PQ Labs multi-touch overlay is Plug-and-play solution for both developers and end-users. Exceptional durability and accuracy.

## PQ Labs Multi-Touch Wall

PQ Labs 100" - 250" (20 ft wide) interactive wall was designed to fit presentations and broadcast uses. It delivers remarkable impression not found in traditional large scale solutions.

## Multi-Touch OEM Components

Designed for a wide range of screen sizes. Exceptionally reliable solution supporting up to 32 touch points

## SPECIFICATION

<b>Available Sizes:</b>	32", 40", 42", 46", 50", 52", 55", 57", 60", 65" (Custom sizes available upon request)
<b>Glass:</b>	3mm tempered glass (Custom versions available upon request)
<b>Frame Color:</b>	Piano Black or Black powered-coated. (Custom colors available upon request)
<b>Touch Points:</b>	Detects up to 32 points simultaneously
<b>Touch Technology:</b>	PQLabs LED Cell Imaging
<b>Touch Method:</b>	Finger, gloved hand or any other pointer. Stylus minimum 6mm tip. Object shape recognition (Palm, fist recognitions)
<b>Construction:</b>	Aluminum, tempered glass, printed circuit boards
<b>Luminous Transmission:</b>	Better than 95% with glass
<b>Touch Activation Force:</b>	No pressure required
<b>Finger Touch accuracy:</b>	±1.5mm
<b>Touch Durability:</b>	Unlimited
<b>Touch Response Time:</b>	7ms - 12ms
<b>Environment:</b>	Operating temperature: 0°C to 55°C; Storage temperature: -25°C to 85°C Operating humidity: 10% to 90% RH, non-condensing; Storage humidity: 10% to 90% RH, non-condensing
<b>Power Supply:</b>	USB Powered (for screen size ≤ 52") Dual USB Powered (for screen size ≥ 65")
<b>Interface:</b>	USB 2.0 (Full speed), compatible with USB 1.1 port, HID compliant, plug-and-play compatible
<b>OS:</b>	Windows 2000, XP, Vista, Windows 7, Mac OS X
<b>Connection Options:</b>	USB Series A
<b>Warranty:</b>	1 year parts and labor